



Product Data

Alphasyn PG

Synthetic gear oils

Description

The Castrol Alphasyn™ PG gear oil range of synthetic lubricants are based on polyalkyleneglycol (PAG) fluids enhanced with antioxidants, rust inhibitors and Extreme Pressure (EP) additives of high thermal stability.

Application

Alphasyn PG gear oils are primarily intended for use in worm reduction gear boxes, where the low coefficient of friction of the PAG base fluid improves efficiency and consequently reduces power consumption and operating temperatures. This is particularly important in applications where sliding contact is high. The use of a PAG base stock provides inherently high Viscosity Index (VI) and low pour points making these products suitable for use over a wide temperature range. Alphasyn PG meets the requirements of most OEM's that allow the use of PAG based gear oils.

Advantages

- Low coefficient of friction reduces energy consumption and lowers operating temperatures, this leads to longer oil life.
- Good thermal and oxidative stability provides reliable operation and extended operating life when compared to mineral oil based products.
- Inherently high VI makes the product suitable for operations over a wide temperature range.
- High load carrying capacity and good wear protection reduces maintenance.

Typical Characteristics

Name	Method	Unit	PG 150	PG 220	PG 320	PG 460
Density @ 15°C / 59°F	ISO 12185 / ASTM D4052	kg/m ³	1050	1060	1060	1060
Kinematic Viscosity @ 40°C / 104°F	ISO 3104 / ASTM D 445	mm ² /s	150	220	320	460
Kinematic Viscosity @ 100°C / 212°F	ISO 3104 / ASTM D 445	mm ² /s	28	40	56	80
Viscosity Index	ISO 2909 / ASTM D2270	-	225	235	240	255
Pour Point	ISO 3016 / ASTM D97	°C/°F	-39/ -38.2	-39/-38.2	-36/ -32.8	-36/ -32.8
Flash Point - closed cup method	ISO 2719 / ASTM D93	°C/°F	210/410	210/410	210/410	210/410
Foam Sequence I - tendency / stability	ISO 6247 / ASTM D892	ml/ml	10/0	10/0	10/0	10/0
Rust test - distilled water (24 hrs)	ISO 7120 / ASTM D665A	-	Pass	Pass	Pass	Pass
Timken OK Load test	ASTM D2782	kg/lb	29.5/65	31.8/70	36.3/80	38.6/85
FZG Gear Scuffing test - A/8.3/90	ISO 14635-1	Failure Load Stage	-	-	>12	>12

Subject to usual manufacturing tolerances.

Additional Information

Normal industrial paints are not compatible with these lubricants. Gearboxes should be left unpainted internally, or alternatively should be painted with two component coatings such as epoxy resins. Care must be taken that seal materials are compatible with these lubricants. The recommended materials are nitrile rubber (NBR), silicone (VMQ), fluoro-silicone rubber (FMQ), and fluoroelastomers (FKM). Incompatible materials are likely to shrink or swell, thus causing either severe leakage or seizure of the seal. These products are not miscible with mineral oils.

Alphasyn PG
05 Nov 2024
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

<http://msdspds.castrol.com>