



# CT EP LITHIUM COMPLEX GREASE

## DESCRIPTION

A multipurpose high temperature grease made from highly refined high viscosity mineral base oils thickened by lithium complex soap, and fortified with extreme pressure, anti-rust and anti-oxidation additives. The grease possesses good water-resistance, high working temperature, excellent chemical and mechanical stability for use in heavy duty automotive and industrial equipment under severe working conditions.

## BENEFITS

- High drop point, suitable for working at higher temperature
- Excellent EP, protects parts from damage under heavy and/or shock loads
- Outstanding water resistance, minimizes water wash out
- Good pump-feeding characteristic
- Good anti-oxidation and anti-rust properties, extends service life

## APPLICATION

Recommended for lubrication of automotive wheel bearings and chassis in heavy-duty trucks and vehicles, construction and other industrial equipment operating under heavy load and working temperature range from -20°C to 180°C.

## TYPICAL SPECIFICATION

NLGI Number	NO.2
Colour	Blue
Type of Thickener	Lithium Complex
Drop Point, °C,	315
Penetration, @25°C Worked, 0.1mm	255
Four-ball Weld Load, kgf	315
Oil Separation, @100°C, 24hrs, %wt	0.5
Water washout, @79°C, 1hrs, %wt	2.0
Copper Corrosion, 100°C, 24hrs	1b
Rust Prevention	Pass