



Transmax ATF DEXRON®-VI MERCON® LV Multivehicle

Automatic Transmission Fluid

Description

Castrol Transmax ATF DEXRON®-VI MERCON® LV Multivehicle, formulated with Smooth Drive Technology™, is designed for modern automatic transmissions. Its superior technology enables longer transmission life. It is approved and licenced by GM and Ford for use in vehicles requiring their latest ATF specifications and is also suitable for use in most Asian and European automatic transmissions. Transmax ATF DEXRON®-VI MERCON® LV Multivehicle, formulated with Smooth Drive Technology™, delivers enhanced protection and gives drivers a smoother drive for longer.

Advantages

- OEM approved and licensed by Ford (MERCON® LV) and GM (DEXRON®-VI)
- Low viscosity formula for maximum fuel efficiency in modern automatic transmissions
- Enhanced friction durability for smooth transmission performance
- Superior high temperature protection to effectively resist oxidation
- Recommended for use in most automatic transmissions

Typical Characteristics

Name	Method	Units	Typical Characteristics
Density @ 15C, Relative	ASTM D4052	g/ml	0.841
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	5.9
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	30.2
Viscosity Index	ASTM D2270	None	161
Viscosity, Brookfield @ -40C (75W)	ASTM D2983	mPa.s (cP)	10000
Pour Point	ASTM D97	°C	-54
Flash Point, COC	ASTM D92	°C	218

Product Performance Claims

MERCON® LV

DEXRON® -VI

Suitable for use where JASO 1A(03)

JASO 1A LV(13) is required including:

Toyota T III, T IV, WS

Mitsubishi SP II, IIM, III, IV, PA, J3

Mazda ATF M-III, M-V, FZ

Honda/Acura DW 1/Z 1

Nissan Matic D, J, S

JWS 3314/3317/ 3309

Suzuki AT Oil 5D06, 2384K

Isuzu

Subaru F6, Red 1

Daihatsu AMMIX ATF D-III Multi D3-SP

Hyundai/Kia SP III, SP IV

MB 236.10, MB 236.12, MB 236.14 & 236.15 236.41, 236.16 & MB 236.17

BMW ETL 7045, 7045 E, LA 2634, LT 71141, ZP 5 HP 30, ETL 8072B, GA6L45R, GA6HP19Z, GA6HP19ZTU,

GA6HP26Z, GA6H-P26ZTU, GA6HP32Z, S6S53BZ, GA8HP45Z, GA8HP70Z, GA8HP90Z & GA7AHSCD

Also suitable for use in 6, 8 and 9-speed automatics from Audi, BMW, Mini-Cooper, Jaguar, Peugeot/

Citroen, Saab, Volvo, VW, Porsche. 7 and 9 speed automatics from Mercedes Benz and all vehicles where

Dexron III or Mercon SP is required.

Commercial Vehicle Also suitable for use where the following OFF-ROAD application is required:

Volvo AT 102

Transmax ATF DEXRON®-VI MERCON® LV Multivehicle

24 Aug 2022

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Castrol Lubricants (Malaysia) Sdn. Bhd., Registration No. 198701007157 (165875-W), Level 9, Tower 5, Avenue 7, The Horizon Bangsar South City No.8,

Jalan Kerinchi, 59200 Kuala Lumpur

Phone No : 03-22818181 Toll free Line: 1-800-88-0018

www.castrol.com