

SUPERDRAULIC®

ANTI WEAR HYDRAULIC OIL - 32, 46, 68

DESCRIPTION

Superdraulic® is a range of high performance anti wear hydraulic oils. They have been formulated using highly refined base oils fortified with zinc anti wear, oxidation corrosion inhibitors and anti foam additives.

This produces a highly thermally stable fluid capable of handling high loads and high temperatures. The Superdraulic® range is available in ISO grades 32, 46, and 68.

COMPATIBILITY

Superdraulic® is compatible with most pumps, valves, and seal materials. However, like all hydraulic oils containing zinc anti wear additives, it is not suitable for use with pumps having silver plated parts (e.g. some Lucas units).

SUMMARY OF BENEFITS

- Improved equipment life and decreased downtime due to superior wear and corrosion protection
- Enhanced chemical and thermal stability provide long fluid life and permit higher operating temperatures
- Excellent air release and antifoam properties to prevent cavitation and oxidation
- Excellent filterability even when contaminated, thereby preventing filter blockages. This saves filter replacement costs and down time
- Enhanced low frictional characteristics to prevent the occurrence of "stick slip"

SPECIFICATIONS

Superdraulic® meets the following international performance specifications:

- ISO Viscosity Grades 32, 46, 68,
- Cincinnati Milacron P68, P69, P70
- Denison HF-0, HF-1, HF-2
- DIN 51 524 Part 2 (HLP type oils)
- US Steel 136, 127
- Vickers 1-286-S, M2952-S

Superdraulic® meets the requirements of the following pump manufacturers:

- | | |
|-------------------------|-------------|
| • Hagglund | • Rexroth |
| • Danfoss | • Linde |
| • Bosch | • Racine |
| • Commercial Hydraulics | • Vickers |
| • Cincinnati Milacron | • Denison |
| • Oilgear | • Sunstrand |

SUPERDRAULIC®

ANTI WEAR HYDRAULIC OIL - 32, 46, 68

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

TYPICAL CHARACTERISTICS

SUPERDRAULIC®	Test Method	Units	32	46	68
Density @ 15°C	ASTM D1298	kg/L	0.866	0.869	0.876
Kinematic Viscosity					
@ 40°C	ASTM D445	cSt	30.6	45.5	65.7
@ 100°C	ASTM D445	cSt	5.3	6.7	8.5
Viscosity Index	ASTM D2270	-	106	99	99
Pour Point	ASTM D97	°C	-12	-12	-9
Flash Point (COC)	ASTM D92	°C	218	224	226
FZG Gear Test (A/8.3/90°C)	IP 334	Stage Failure	10	10	10
Colour	ASTM D1500	-	1.0	1.0	1.0

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

32: IBC - 300172

46: IBC - 300173

68: IBC - 300174

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

Phone: 02 9673 9600 - **Fax:** 02 9623 6466 - **Email:** sales@gulfwestern.com.au - **Web:** www.gulfwestern.com.au

ACN: 087 558 398