

DESCRIPTION

Top Dog 15W-40 CF-4/SG is a heavy duty multi-grade engine oil that offers high levels of protection for engines operating on diesel, petrol or LPG. The combination of premium quality base stocks and high performance additives results in an engine oil with high versatility in a range of on and off-road applications. Top Dog 15W-40 CF-4/SG provides high levels of protection against wear and corrosion. Top Dog 15W-40 CF-4/SG has been formulated to meet the needs of both naturally aspirated or turbo charged diesel engines, petrol engines or engines operating on LPG calling for API CF-4 /SG or earlier specifications.

Top Dog 15W-40 CF-4/SG is suitable for many on and off-highway applications including construction, forestry, mining, marine and for stationary engines including those used for power generation. The high TBN reserve and exceptional soot handling of Top Dog 15W-40 CF-4/SG makes it suitable for use with both low or high sulphur fuels.

SPECIFICATIONS

- SAE 15W-40
- API CF-4/SG

SUMMARY OF BENEFITS

- Premium performance and protection in all conditions
- High level of soot and wear control
- Robust reserve alkalinity (TBN) and high performing dispersant chemistry for good acid neutralization and sludge control
- Enhanced frictional properties result in improved fuel economy and extended engine life
- Excellent, stay-in-grade performance ensure viscosity integrity and reduced oil consumption across the drain interval

| TOP DOG 15W-40 CF-4/SG | TEST METHOD | UNITS | RESULTS |
|----------------------------|-------------|---------|---------|
| DENSITY @ 15°C | ASTM D1298 | kg/L | 0.876 |
| KINEMATIC VISCOSITY | | | |
| @ 40°C | ASTM D445 | cSt | 107.9 |
| @ 100°C | ASTM D445 | cSt | 15.2 |
| VISCOSITY INDEX | ASTM D2270 | - | 148 |
| APPARENT VISCOSITY @ -20°C | ASTM D5293 | cP | < 7000 |
| COLOUR | ASTM D1500 | - | 2.5 |
| POUR POINT | ASTM D97 | °C | -33 |
| FLASH POINT (COC) | ASTM D92 | °C | 230 |
| TOTAL BASE NUMBER | ASTM D2896 | mgKOH/g | 11 |

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

AVAILABLE PACK SIZES

1000LT - #300253B

August 2024