

AP ATF DIII

PREMIUM AUTOMATIC TRANSMISSION FLUID

DESCRIPTION

AP ATF DIII is a premium automatic transmission fluid designed for modern automatic gearboxes. The oil is blended with highly refined base oils and select additives to enhance oxidation stability, anti-friction, anti-wear and low temperature properties and low temperature fluidity. The oil meets the performance specifications of GM DEXRON III, Ford MERCON, Caterpillar TO-2, Allison C-4.

CHARACTERISTICS

- Excellent modifying friction
- High shear stability
- Excellent low temperature performance
- Superior thermal and oxidation stability
- Outstanding foam resistance

APPLICATION

AP ATF DIII is recommended for use in modern passenger cars and light trucks where Dexron III is required. It can also be used as hydraulic fluid in some automatic systems and Vickers pumps.

TYPICAL SPECIFICATION

GRADE		III
Kinematic Viscosity, cSt		
@ 40°C	ASTM D445	35
@ 100°C	ASTM D445	7.6
Viscosity Index	ASTM D2270	165
Flash Point (COC), °C	ASTM D92	170
Pour Point, °C	ASTM D97	-32



環球石油

AP Oil International Limited

30 Gul Crescent, Jurong, Singapore 629535

tel 65 6861 5503 fax 65 6861 9162

www.apoil.com.sg

Due to continuous research and development, the above typical data is subject to change without notice. The information should not be regarded as legally binding assurance of any properties or suitability for any particular application.