

AP GETOEL EP SYNTEC

SYNTHETIC AUTOMOTIVE GEAR OIL

DESCRIPTION

AP GETOEL EP SYNTEC is synthetic automotive gear oil meeting the performance requirements of API GL-4. The oil exhibits good wear protection, anti-rust, anti-corrosion and excellent demulsification and foaming resistance properties. It is environmental friendly which contains neither lead nor chlorine.

BENEFITS

- High viscosity index enables wide working temperature
- Excellent oxidation and thermal stability provides long service life
- Excellent rust and corrosion inhibition
- High extreme pressure exhibits good load-carrying capability

APPLICATION

AP GETOEL EP SYNTEC is suitable for all gears in passenger cars and other automotive transmission systems operating under wide temperature range.

TYPICAL SPECIFICATION

SAE Grade		75W/80
Kinematic Viscosity,		
@ 40°C, cSt	ASTM D445	47
@ 100°C, cSt	ASTM D445	8.3
Viscosity Index	ASTM D2270	156
Flash Point (COC), °C	ASTM D92	205
Pour Point, °C	ASTM D97	-42

V.012016



環球石油

AP Oil International Limited
 30 Gul Crescent, Jurong, Singapore 629535
 tel 65 6861 5503 fax 65 6861 9162
 www.apoil.com.sg

Due to continuous research and development, the above typical data is subject to change without notice. The information should not be regarded as legally binding assurance of any properties or suitability for any particular application.