

AP GETOEL EP

INDUSTRIAL EP GEAR OILS

DESCRIPTION

AP GETOEL EP are premium extreme pressure industrial gear oils containing anti-oxidation, anti-corrosion, anti-wear and anti-foam inhibitors. These oils meet the performance requirements of USS 224, AGMA 9005-D94, DIN 51517 Part 3, Cincinnati Milacron P-59 and pass FZG 12th stage test, etc. They are environmental friendly containing neither lead nor chlorine.

CHARACTERISTICS

- Superior load-carrying EP capability
- Good thermal and oxidation stability
- Excellent anti-rust and anti-corrosion properties
- Outstanding protection against wear and shock
- Prolongs gear equipment life

APPLICATION

AP GETOEL EP are recommended for all types of industrial gear both enclosed and open. Also suitable for lubrication of systems containing worm gears, bearings, sliding parts, etc.

TYPICAL SPECIFICATION

ISO GRADE		68	100	150	220	320	460	680	1000	
Kinematic Viscosity, cSt										
	@ 40°C	ASTM D445	68	100	150	220	320	460	680	1000
	@ 100°C	ASTM D445	8.7	11.4	15.1	19.5	25.1	30.9	39.0	46.0
Viscosity Index	ASTM D2270	100	99	99	99	99	98	92	85	
Flash Point, °C	ASTM D92	218	233	240	245	247	250	260	266	
Pour Point, °C	ASTM D97	-10	-10	-10	-9	-8	-6	-6	-5	



環球石油

AP Oil International Limited

30 Gul Crescent, Jurong, Singapore 629535

tel 65 6861 5503 fax 65 6861 9162

www.apoil.com.sg

Due to continuous research and development, the above typical data is subject to change without notice. The information should not be regarded as legally binding assurance of any properties or suitability for any particular application.