

AP PNEUMATICO

ROCK DRILLING OILS

DESCRIPTION

AP PNEUMATICO are premium rock drilling oils formulated with highly refined base oils and select additives to impart the non-drip, oiliness, anti-wear characteristics. The oils provide excellent lubricity and EP properties.

BENEFITS

- Excellent oiliness and non-drip
- Exhibit extra EP and load carrying capabilities
- Excellent operating performance of hydraulic systems
- Highly effective in controlling wear, oxidation and corrosion

APPLICATION

AP PNEUMATICO are recommended for use in rock drilling and all percussion types of pneumatic tool.

TYPICAL SPECIFICATION

ISO Grade		32	46	68	100	150	320
Kinematic Viscosity,							
@ 40°C, cSt	ASTM D445	32	46	68	100	150	320
@ 100°C, cSt	ASTM D445	5.4	6.8	9.3	10.8	14.9	25.0
Viscosity Index	ASTM D2270	108	100	100	99	98	98
Flash Point (COC), °C	ASTM D92	200	200	210	220	250	268
Pour Point, °C	ASTM D97	-15	-12	-10	-10	-10	-9

V. 072013



環球石油

AP Oil International Limited

30 Gul Crescent, Jurong, Singapore 629535

tel 65 6861 5503 fax 65 6861 9162

www.apoil.com.sg

Due to continuous research and development, the above typical data is subject to change without notice. The information should not be regarded as legally binding assurance of any properties or suitability for any particular application.