

AP SUPER DIESELUBE CF

HEAVY-DUTY DIESEL ENGINE OILS

DESCRIPTION

AP SUPER DIESELUBE CF are high speed, heavy duty diesel engine oils formulated with highly refined mineral base oils and select additives to enhance oxidation stability and protection against wear and corrosion. These oils meet the performance requirements of API CF, Allison C-4 and Caterpillar TO-2, etc.

BENEFITS

- High thermal and oxidation stability
- Good detergency and dispersancy properties
- Effective control of piston deposits, wear and corrosion
- Keeping engine clean

APPLICATION

AP SUPER DIESELUBE CF are recommended for naturally aspirated, turbo-charged or supercharged diesel engines of heavy duty vehicles, commercial trucks, construction machineries. 10W grade can also be used as hydraulic oils for heavy machinery.

TYPICAL SPECIFICATION

SAE Grade		10W	30	40	50	
Kinematic Viscosity,	@ 40°C, cSt	ASTM D445	46	99	140	202
	@ 100°C, cSt	ASTM D445	7.3	10.8	14.5	18.5
Viscosity Index	ASTM D2270	99	97	97	95	
Flash Point (COC), °C	ASTM D92	212	230	245	263	
Pour Point, °C	ASTM D97	-12	-12	-12	-9	

V. 072013



環球石油

AP Oil International Limited

30 Gul Crescent, Jurong, Singapore 629535

tel 65 6861 5503 fax 65 6861 9162

www.apoil.com.sg

Due to continuous research and development, the above typical data is subject to change without notice. The information should not be regarded as legally binding assurance of any properties or suitability for any particular application.