

Product Data Sheet (PDS)

1 Mar 2019

Page 1 of 1



Product: AceRev® AdBlue® Solution

Application: Used in automotive Selective Catalytic Reduction (SCR) system to reduce Nitrogen Oxides (NOx) in diesel engine exhaust gas.

Parameters	Unit	Values
Urea content	% (m/m)	31.8 - 33.2
Refractive index at 20°C	-	1.3814 - 1.3843
Alkalinity as NH3	% (m/m)	<0.2
Biuret	% (m/m)	<0.3
Aldehydes	mg/kg	<5.0
Insoluble matter	mg/kg	<20.0
Phosphate(PO4)	mg/kg	<0.5
Aluminium	mg/kg	<0.5
Calcium	mg/kg	<0.5
Chromium	mg/kg	<0.2
Copper	mg/kg	<0.2
Iron	mg/kg	<0.5
Potassium	mg/kg	<0.5
Magnesium	mg/kg	<0.5
Sodium	mg/kg	<0.5
Nickel	mg/kg	<0.2
Zinc	mg/kg	<0.2

The analytical methods are defined in ISO22241-2 (version 2019).

Manufactured and quality controlled in Singapore by Interior Pte Ltd.

AceRev® is a registered trademark of Interior Pte Ltd.

AdBlue® is a registered trademark of the Verband der Automobilindustrie e.V (VDA).